

# Trailer Specifications

- Trailer Fitted With Resin Coated Plywood Platform
- Aluminium Treadplate Platform Covering
- Removable Headboard, Dropsides & Tailboard
- Removable Headboard
- Removable Ladder Rack (Only Available With Headboard)
- 6' Long Perforated Galvanized Steel Skids (Pair) (Including Prop Stands)
- 6' Long Aluminium Skids (Pair) (Including Prop Stands)
- 8' Long Perforated Galvanized Steel Skids (Pair) (Including Prop Stands)
- 8' Long Aluminium Skids (Pair) (Including Prop Stands)
- Weldmesh Panelled Side Extensions
- Weldmesh Centre Pillar Tie-Bar
- Full Width Loading Ramp (6') With Assistor (Including Prop Stands)
- Lashing Ring (Recessed) Pair

## Flat-bed Trailers

LT Series	Maximum Gross Weight	Tyres	Unladen weight													
LT85	2000kg	145R10C	430kg	Option	Option	Option	Option	Option	Option	-	-	Option	-	Option	Option	
LT105	2000kg	145R10C	500kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LT125	2000kg	145R10C	545kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LT106	2000kg	145R10C	535kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LT126	2000kg	145R10C	582kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LT146	2000kg	145R10C	632kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option

## LM 5-Series

LM85	2700kg	185/60R12C	470kg	Option	Option	Option	Option	Option	Option	-	-	Option	Option	Option	Option	
LM105	2700kg	185/60R12C	527kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LM125	2700kg	185/60R12C	571kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option

3500kg Gross version available (add 30kg<sup>†</sup>)

## LM 6-Series

LM106	3500kg	185/60R12C	600kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LM126	3500kg	185/60R12C	641kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LM146	3500kg	185/60R12C	675kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LM147	3500kg	185/60R12C	772kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LM166	3500kg	185/60R12C	761kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LM167	3500kg	185/60R12C	852kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LM186	3500kg	185/60R12C	821kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option
LM187	3500kg	185/60R12C	906kg	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option	Option

Tri-axle version available (14', 16' & 18' only, add 110kg<sup>†</sup>)

## Beavertail Trailers

LT146/B	2000kg	145R10C	630kg	Option	Option <sup>†</sup>	Option	Option	Option	Option	-	-	-	-	Option	Option	
<b>Beavertail</b>																
LM146/B	3500kg	185/60R12C	685kg	Option	Option <sup>†</sup>	Option	Option	Option	Option	-	-	-	-	Option	Option	
LM147/B	3500kg	185/60R12C	785kg	Option	Option <sup>†</sup>	Option	Option	Option	Option	-	-	-	-	Option	Option	
LM166/B	3500kg	185/60R12C	710kg	Option	Option <sup>†</sup>	Option	Option	Option	Option	-	-	-	-	Option	Option	
LM167/B	3500kg	185/60R12C	810kg	Option	Option <sup>†</sup>	Option	Option	Option	Option	-	-	-	-	Option	Option	

## Tiltbed Trailers

CT166	3500kg	185/60R12C	825kg	Option	Option*	Option	Option	-	-	-	-	Option	Option	-	Option	
CT167	3500kg	185/60R12C	950kg	Option	Option*	Option	Option	-	-	-	-	Option	Option	-	Option	

Extra high ramps (3' high) - CT166G - CT167G (add 30kg<sup>†</sup>)

\*Excludes tailboard as standard ramp (1' high) is included

<sup>†</sup>This option must be specified at time of order due to special chassis. Factory fit only.

<sup>‡</sup>Add to unladen weight

All trailer weights are unladen and include standard options, these weights are for guidance only.

# Trailer Specifications

Trailer With Drop Tailboard

Trailer With Loading Ramp

Trailer With Hinged Skids

Aluminium Treadplate Platform Covering

Weldmesh Panelled Side Extensions (Loading Ramp Models Only)

Weldmesh Panelled Side Extensions (Tailboard Models Only)

Ladder Rack

Prop Stands (Pair)

Integral Ramp/Skid Support

8' Long Perforated Galvanized Steel Skids (Including Prop Stands)

8' Long Aluminium Skids (Pair) (Including Prop Stands)

Lashing Ring (Recessed) Pair

## General Duty Trailers

	Maximum Gross Weight	Tyres	Unladen weight	Unladen weight	Unladen weight									
<b>GD 4-Series</b>														
GD64 Single Axle	1400kg	165R13C	307kg	329kg	-	Option	Option	Option	Option	Std	-	-	-	Option
GD84 Single Axle	1400kg	165R13C	332kg	354kg	-	Option	Option	Option	Option	Std	-	-	-	Option
GD84 Single Axle	1500kg	175/75R16C	375kg	397kg	-	Option	Option	Option	Option	Std	-	-	-	Option
GD84 Single Axle	1500kg	6.50R16C	385kg	407kg	-	Option	Option	Option	Option	Std	-	-	-	Option
GD84TA Twin Axle	2700kg	165R13C	405kg	428kg	-	Option	Option	Option	Option	Option	-	-	-	Option
<b>GD 5-Series</b>														
GD85 Single Axle	1400kg	165R13C	365kg	400kg	-	Option	Option	Option	Option	Std	-	-	-	Option
GD85	2700kg	165R13C	440kg	475kg	-	Option	Option	Option	Option	Option	-	-	-	Option
GD105	2700kg	165R13C	495kg	530kg	-	Option	Option	Option	Option	Option	-	-	-	Option
GD125	2700kg	165R13C	557kg	592kg	-	Option	Option	Option	Option	Option	-	-	-	Option
<b>GD 6-Series</b>														
GD106	3500kg	175/75R16C	692kg	740kg	-	Option	Option	Option	Option	Option	-	-	-	Option
GD126	3500kg	175/75R16C	760kg	808kg	-	Option	Option	Option	Option	Option	-	-	-	Option
GD106	3500kg	6.50R16C	702kg	750kg	-	Option	Option	Option	Option	Option	-	-	-	Option
GD126	3500kg	6.50R16C	770kg	818kg	-	Option	Option	Option	Option	Option	-	-	-	Option

## Tipping Trailers

TT85 (Manual Pump)	2700kg	165R13C	730kg	-	-	Option*	-	Option	Std	-	-	-	-	Option
TT85E Power-Tip	2700kg	165R13C	730kg	-	-	Option*	-	Option	Std	-	-	-	-	Option
TT105 Power-Tip	3500kg	185/60R12C	975kg	-	-	Std*	-	Option	Std	Option	-	Option	Option	Option
TT126 Power-Tip	3500kg	185/60R12C	1165kg	-	-	Std*	-	Option	Std	Option	-	Option	Option	Option

\*Plain Aluminium Covering

## Plant Trailers

GP106M Maxi Plant	3500kg	155/70R12C	-	-	690kg	Option	-	-	-	Std	-	-	-	Std (4)
GP126M Maxi Plant	3500kg	155/70R12C	-	-	755kg	Option	-	-	-	Std	-	-	-	Std (4)
GX84 Skids	2700kg	165R13C	-	-	535kg	Option	-	-	Option	Std	-	-	-	Option
GX84 Ramp	2700kg	165R13C	-	540kg	-	Option	Option	-	Option	-	Std	-	-	Option
GX105 Skids	2700kg	165R13C	-	-	665kg	Option	-	-	Option	Std	-	-	-	Option
GX105 Ramp	2700kg	165R13C	-	665kg	-	Option	Option	-	Option	-	Std	-	-	Option
GX105 H/D Skids	3500kg	155/70R12C	-	-	705kg	Option	-	-	Option	Std	-	-	-	Option
GX105 H/D Ramp	3500kg	155/70R12C	-	715kg	-	Option	Option	-	Option	-	Std	-	-	Option
GX106 Skids	3500kg	155/70R12C	-	-	700kg	Option	-	-	Option	Std	-	-	-	Option
GX106 Ramp	3500kg	155/70R12C	-	705kg	-	Option	Option	-	Option	-	Std	-	-	Option
GX126 Skids	3500kg	155/70R12C	-	-	775kg	Option	-	-	Option	Std	-	-	-	Option
GX126 Ramp	3500kg	155/70R12C	-	790kg	-	Option	Option	-	Option	-	Std	-	-	Option

H/D - Heavy Duty

All trailer weights are unladen and include standard options, these weights are for guidance only.



### The Ifor Williams commitment to trailer security

Each trailer is fitted with an ID plate which has a unique serial number etched on it. Additionally, the drawbar has a different unique number cut through it<sup>†</sup>, which is virtually impossible to alter without noticeably affecting the appearance of the numbers and galvanized finish.

### Other optional extras

(LT, LM & GD models)

- Braked Manual winch 2000kg
- Braked Manual winch 3000kg
- Electric winch
- Canopy (GD Models)

**ALL IFOR WILLIAMS TRAILERS NOW INCLUDE SPARE WHEEL FITTED AS STANDARD**

<sup>†</sup>Excludes GD range.